

## Handheld Particle Counter CTZ-PC-H630



The Handheld Particle Counter **CTZ-PC-H630** is reliable and easy to use. It is handheld, ergonomically designed, and light. **CTZ-PC-H630** simultaneously counts airborne particles in six different size ranges. It has a 480×320 high-resolution colorful LCD screen. The count data is displayed on the screen as the total number of particles (cumulative count). Data can be easily downloaded to a computer or printed with an optional printer.

You can move the particle counter to a point you want. With this device, it is very easy to measure at any point you want and to obtain accurate results. You can instantly print the results or save them to a computer. The large colorful LCD screen allows you to view the data easily and without errors.

## Features

- 0.1 CFM (2.83 L/min) flow rate
- Six particle-size channels  $(0.3/0.5/1.0/2.0/3.0/5.0 \mu m)$
- ♦ 480×320 High-resolution colorful LCD display.
- ♦ The LCD display shows battery capacity.
- ♦ High capacity USB rechargeable Li-ion battery
- ♦ Internal audible alarm (the alarm channel can be chosen arbitrarily)
- ♦ 95% UCL Calculation.
- ♦ Large memory for storing data, Up to 260,000 records.
- ◆ The data easily downloaded to a computer by free software. Able to export the file of each report to office excel.
- Lightweight (0.9 kg)
- External function module: temperature and humidity, differential pressure, Air velocity(Optional).
- Supplied with free Carrying Case.



## Handheld Particle Counter CTZ-PC-H630

S				, A	,				
	n	e	C1	H	C	<b>a</b> 1	11	O.	n
$\boldsymbol{\mathcal{O}}$	μ	v	ىب		·	a	ш	v.	ΙТ

Specification					
Part Number	CTZ-PC-H630				
Product Name	Handheld Particle Counter				
Flow rate	0.1 CFM (2.83 L/min)				
Channels	6 Channels (0.3/0.5/1.0/2.0/3.0/5.0μm)				
Light source	Laser diode				
Calibration particles	SIMT certification				
Max. concentration	2,000,000/ft3				
Zero count	<1 per 5 min.				
Counting efficiency	50% @ 0.3μm, 100%@0.5μm				
Communication modes	USB				
User interface & display	480x320 High-resolution colorful LCD display				
Data display modes	y modes Counts, Counts/m3, Counts/ft3				
Sampling modes	Manual repeated, Auto for UCL calculation (calculation for all 6 channels)				
Error messages (real-time)	Exceeds alarm limits ,battery status indication				
External software	Easy upload to PC				
Data storage	Up to 260,000 records				
External surface	ABS (plastic resin)				
Dimensions (WxHxD)	23x13x4.5(cm)				
Weight	0.9kg				
Power	AC adapter:100-240 VAC, 50/60 Hz				
Batteries	3.7V Li-on rechargeable battery 10000mAH				
Operating time on battery	More than 8hr for sampling				
Battery recharging	USB				
Operating temperature	0 - 35°C				
Operating humidity	0 - 85%				
Accessory supplied Free	Case, Operation manual, Factory Calibration certificate, Filter, min USB cable, Charger, Isokinetic Probe, Fuse.				



## **Ordering Information**

Part Number	Description
CTZ-PC-H630	Handheld Particle Counter
	Content; Case, Operation manual, Factory Calibration
	certificate, Filter, min USB cable, Charger, Isokinetic
	Probe, Fuse.